

# GODZILA PTE LTD/ Singapore

## **B SMT Fipper unit ( PCB 180 degree turn)**

- i Strong , firm and stable Modular design .
- ii Microcomputer touch screen Panasonic, Japanese Mitsubishi PLC control system
- iii PCB positioning: controlled by high-precision servo motor photoelectric sensor
- iv PCB positioning: controlled by high-precision servo motor photoelectric sensor
- vi PCB transport direction: Right → Left or Left → Right.

### **SPECIFICATION**

<b>Sizes</b>	<b>M</b>	<b>L</b>	<b>LL</b>	<b>XL</b>
Model	GH-250F-M	GH-330F-L	GH-390F-LL	GH-460F-XL
Ext. Dimension (mm)	600 x 690 x 1150	600 x 770 x 1150	600 x 830 x 1150	600 x 900 x 1150
PCB Min. size (mm)		50 x 50		
PCB Max. size (mm)	350x250	450x 330	520 x 390	520 x 460
Mag. Rack Dim.(mm)	355x320x563	460x400x565	535x460x570	535x530x563
Control System	Industril Module Card system ( PLC option)			
Communication	SMEMA for bothin & out			
Power Supply	Single phase AC 220V with 50/60Hz			
Weight ( Standard) kg	200	210	220	230

